

WACHS UTILITY 18 HP CE COMPLIANT HPU



GAS #14-000-18

Wachs Utility 18 H.P. CE Compliant, Gas Engine Driven hydraulic cart. Powered by an 18 hp(13.25 kW) Briggs & Stratton V-Twin engine with electric start, it is designed to power both HTMA Class I & Class II tools. A selector valve on the control panel sets the pump to deliver either 8gpm (30 lpm) @ 2,000 psi (140 bar) or 5 gpm (20 lpm) @ 2,000 psi (140bar).

FEATURES

- Fuel Tank capacity: 5.5 gallon (20 l). Minimum grade 85 octane
- One 5 gpm (19 lpm) Circuit or One 8 gpm (30 lpm) Circuit
- L 36 in (91.4cm) x W 23 in (58.4cm) x H 29.5 in (74.9cm)
- 330 lbs (149.6kg) weight
- Hydraulic Reservoir Capacity 3 gallon (11 l)
- Heat Rejection 5 hp
- HTMA/EHTMA Category Type 1 and 2
- Max Pressure 2000 psi (138 bar)
- Auto idle feature-lower fuel consumption & less noise
- Tool circuit lockout during engine start-up - safety feature
- Quartz hour meter on control panel-records engine run time
- Lift and latch handle with fold up side handles
- 35 Ah sealed, non spillable, no maintenance battery located in covered compartment
- Electric start engine has pressure lubrication system, low engine oil shutdown & spin-on oil filter
- In-tank hydraulic filter with dipstick & easy access filter replacement

Recommended Hydraulic ISO 32 Oil



Wachs Utility 18 HP CE Compliant gas-powered HPU is portable & easy to setup