



The Standard LX, an E.H. Wachs exclusive valve maintenance trailer, comes with our industry-leading ERV-750 extended reach valve exerciser, our newest controller – the HC-100 wireless handheld computer / controller/ datalogger with GPS and Vitals software. Also equipped with the powerful 500CFM-11in HG vacuum with hydraulic slide, tilt & dump (rear discharge) with latching rear door spoils tank. Loaded with storage and accessories this trailer is ready for serious valve maintenance work.

FEATURES

- 270° of motion, 13ft total extended reach, 750 ft/lbs ERV-750 valve exerciser
- Ruggedized HC-100 controller/data logger with built in GPS
- Available in two types of engines:
Diesel: Tier 4F compliant Kubota 1.1 L, I-3 4-stroke, liquid cooled IDI. #77-000-38
Gas: 27HP Kohler overhead cam, air cooled, #77-000-36
- HTMA Class II circuit, 10 gal reservoir, fan cooled heat exchanger, 8gpm@2000psi
- Positive displacement blower provides 500 CFM-11in Hg vacuum
- 250 gal spoils tank utilizing exclusive hydraulic slide, tilt & dump (rear discharge) with latching rear door
- 2.5 GPM@3000 psi pressure washer system with 95 gallon water tank

INCLUDES

- 2 1/2in, 1 1/4in & 7/8in suction wands
- Short wash down gun
- Long hydro excavation gun
- 20ft suction hose
- 50ft retractable water hose reel

LX PACKAGE BUNDLE

- LED work light & arrow board bar
- 45in auxiliary hydraulic hose reel
- Bluetooth connectivity
- Job box

*Images shown with LX options

SPECIFICATIONS

- Gross Vehicle Weight: 7000 lb (3175 kg)
- Length: 15 ft, Height: 7 ft, Width: 7 1/2 ft



Designed for ease of use, the Standard LX rear-mounted spoils tank gets the job done



2.5GPM@3000 psi pressure washer with 95 gallon water tank makes clean-up easy